



SPREADER

	HURST SP 333 E3	HURST SP 555 E3	HURST SP 777 E3	HURST M 40 E3
Min spreading force (EN)	42 kN	52 kN	63 kN	47 kN
Spreading force, max	836 kN	658 kN	600 kN	500 kN
Spreading distance	23.6 in 600 mm	28.7 in 730 mm	32.0 in 813 mm	40.1 in 1018 mm
Squeezing force, max	144 kN	115 kN	122 kN	
Pulling Force, max	56 kN	58 kN	60 kN	50 kN
Pulling Distance	17.3 in 440 mm	22.4 in 569 mm	25.8 in 655 mm	35.3 in 898 mm
Protection class	IP58	IP58	IP58	IP58
Protection Class Battery	IP68	IP68	IP68	IP68
Battery Ah	5 Ah; 9 Ah*	5 Ah; 9 Ah*	5 Ah; 9 Ah*	5 Ah; 9 Ah*
Saltwater Capability	Yes	Yes	Yes	Yes
Weight with battery	41.1 lbs 18.6 kg	47.2 lbs 21.5 kg	55.1 lbs 25 kg	58.4 lbs 26.5 kg
Weight without battery	37.5 lbs 17.1 kg	43.6 lbs 19.8 kg	51.6 lbs 23.4 kg	54.9 lbs 24.9 kg
Dimension (LxWxH) with battery (*9Ah)	*33.7x10.1x9.96 in 856x256x253 mm	*37.6x10.1x9.96 in 958x265x253 mm	*40.6x12.1x9.96 in 1030x309x253 mm	*44.9x12.1x9.96 in 1140x309x253 mm
Dimension (LxWxH) without battery	32.4x10.1x9.96 in 823x256x253 mm	36.3x10.4x9.96 in 923x265x253 mm	39.3x12.2x9.96 in 997x309x253 mm	43.6x12.1x9.96 in 1106x309x253 mm