

Forestry Multi-Purpose Monitor

Style 3462 300 GPM (1140 LPM)

style 3462 shown
with 3293 125-300
gpm nozzle

The 3462 provides an extremely rugged durable design ideal for a multitude of applications with flows up to 300 gpm (1140 lpm). This compact monitor features a fully sealed integrated electrical control system with waterproof locking connectors for all motors, power and control connections to withstand harsh environments. The high speed motors provide proportional speed control for pinpoint stream positioning and accuracy. With a wide range of available nozzles, the 3462 is ideal for use in water, foam and CAFS applications.

Standard Features:

- CAN proportional speed joystick control
- Lightweight Pyrolite® construction, 23 lbs. (10.4 kg) without nozzle
- Integrated and sealed electronics
- Waterproof (IP 67 rated) locking connectors
- Simple “plug and play” installation
- 320° maximum rotation range with stops at +/- 90°
- 135° maximum elevation range with stops at +45° and -20°
- 12V or 24V (Must Specify)

Nozzle Options:

- Style 3293 low flow adjustable electric fog nozzle with flat disperse spray pattern and flush 30-60-95-125 gpm (115-230-360-475 lpm)
- Style 3293 mid flow adjustable electric fog nozzle with flat disperse spray pattern and 125-175-250-300 gpm (475-660-950-1140 lpm)
- Style 3293 fixed orifice fog nozzles (must specify flow and pressure)
- Quick Attack™ foam tube attachments for Style 3293 fog nozzles
- Smooth bore tips

Style	Weight lbs. (kg)	Height	Weight	Depth	Inlet	Outlet	FLOW GPM	FLOW LPM
3462	23** (10.4 kg)	13 3/16** (335 mm)	11 9/16" (294 mm)	8 29/32" (226 mm)	2" NPT (50 mm)	1 1/2" (38mm)	300	1140

* Base to center of outlet

** Not including nozzle

Additional Options:

- 2" quick disconnect
- Wireless remote control (CAN interface)
- 2" electric valve
- Flat disperse fog pattern available on all Style 3293 nozzles



60350012 ARFF
CAN Joystick



Wireless Remote
Control Available



Style 6037 CAN
Wireless Interface



"Plug and play"
connectors



2" Quick-Disconnect
Ideal for Tilt Cab Trucks