



COMBI

	HURST SC 258 E3	HURST SC 358 E3	HURST SC758 E3
Spreading force at tips	32 kN	40 kN	43 kN
Spreading force, max	700 kN	1500 kN	1500 kN
Spreading distance	12.6 in 321 mm	14.5 in 368 mm	18.7 in 475 mm
Cutter opening	9.2 in	12.2 in 309 mm	15.7 in 400 mm
Cutting force, max	280 kN	492 kN	885 kN
Pulling distance	13.1 in 333 mm	15.0 in 382 mm	13.4 in 340 mm
Pulling force	34 kN	61 kN	94 kN
Removable tips	Yes	Yes	Yes
NFPA Classification	A6 B6 C6 D7 E7 F4	A7 B8 C7 D8 E7 F4	A8 B9 C9 D9 E9 F5
Protection class	IP58	IP58	IP58
Protection Class Battery	IP68	IP68	IP68
Battery Ah	5 Ah; 9 Ah*	5 Ah; 9 Ah*	5 Ah; 9 Ah*
Saltwater Capability	Yes	Yes	Yes
Weight with battery	35.3 lbs 16 kg	44.1 lbs 20 kg	56.4 lbs 25.6 kg
Weight without Battery	31.7 lbs 14.4 kg	40.3 lbs 18.3 kg	53.1 lbs 24.1 kg
Dimension (LxWxH) with battery (*9Ah)	*32.5x8.3x10.0 in 825x210x253 mm	*35.8x9.3x10.0 in 909x235x253 mm	*39.9x10.5x10.0 in 1013x266x253 mm
Dimension (LxWxH) without battery	31.2x8.3x10.0 in 792x210x253 mm	34.5x9.3x10.0 in 876x235x253 mm	38.6x10.5x10.0 in 980x266x253 mm