

KEY	
*	Pyrolite
#	Cast brass
◇	Chrome plated brass



<b>630</b> <b>Angle Elbow</b> SWIVEL FEMALE x MALE
◇ 2 1/2" NH x 2 1/2" NH (65 x 65 mm)




<b>635</b> <b>90° Continuous Swiveling Elbow</b> FEMALE NPT x MALE NH or NPSH
• Full 2" (51 mm) waterway with cast-in turning vane
# 1 1/2" or 2" female x 1 1/2" male (38 or 50 x 38 mm) 4 5/8" length
# 2 1/2" female x 2 1/2" male (65 x 65mm) 5" length



<b>347</b> <b>Hose Plug</b>
• Available with rocker lug
• Chain or jack chain
◇ 1 1/2" NH (38 mm)
◇ 2 1/2" NH (65 mm)



<b>345</b> <b>Hose Cap</b>
• Available with rocker lug
• Chain optional
◇ 1 1/2" NH (38 mm)
◇ 2 1/2" NH (65 mm)



<b>330</b> <b>Short Internal Lug Adapter</b> FEMALE NPT x MALE
◇ 2 1/2" NPT x 2 1/2" NH (65 x 65 mm)



<b>335</b> <b>Double Female Swivel Adapter</b>
* ◇ 2 1/2" NH (65 mm)



<b>336</b> <b>Double Male Adapter</b>
* ◇ 2 1/2" NH (65 mm)



<b>337</b> <b>Rigid Female to Male Adapter</b>
◇ 1" NH x 1 1/2" NH (25 x 38 mm)
◇ 2" NH x 1 1/2" NH (50 x 38 mm)
* ◇ 2 1/2" NH x 1 1/2" NH (65 x 38 mm)



<b>338</b> <b>Suction Lug Adapter with Strainer</b> FEMALE NPT x FEMALE SWIVEL
◇ 1 1/2" NPT x 1 1/2" NH (38 x 38 mm)
◇ 2 1/2" NPT x 2 1/2" NH (65 x 65 mm)

- 1422 Rigid Direct Connect Base**
- For adapting an 1 1/2" nozzle base to a 2 1/2" hose line
  - Pyrolite® construction
  - 2 1/2" female x 1 1/2" male
  - Tapered waterway for reduced turbulence
  - Weight: 12 oz. (340 g)



Style 1422

- 631 60° Angle Elbow**
- For high-rise stand pipes
  - Pyrolite® finish
  - 2 1/2" female x 2 1/2" male
  - Weight: 1 7/8 lbs. (.9 kg)



Style 631

- 650 Swiveling Elbow**
- For aerial applications
  - Pyrolite finish
  - Full flow waterway with cast-in turning vanes for reduced friction loss
  - Available in 4", 5" and 6" sizes
  - Weight: 8 3/4 lbs. (4 kg)



Style 650



### Suction Strainers

#### 339 Basket Suction Strainer

An economical, high capacity suction strainer with galvanized plated mesh for longer life.

- Available in 2 1/2" (65 mm) and 5" (127 mm) size NH and other selected threads
- 2 1/2" (65 mm) barrel strainer length: 4 7/8" (124 mm), weight: 2 lbs. (.9 kg)

#### 340 Barrel Suction Strainer

Heavy-duty barrel suction strainer with rope eye. Capable of flowing large volumes of water to match today's high capacity pumpers.

- Pyrolite® finish
- Available in 4" (102 mm) through 6" (152 mm) NH; 5" (127 mm) weight: 4 1/4 lbs. (1.9 kg)
- 5" (127 mm) barrel strainer length: 10" (254 mm), weight: 4 1/4 lbs. (1.9kg)



Style 339



Style 340

### Hose Jackets

#### 772 2 1/2" (64 mm) Hose Jacket

For emergency repair of burst or leaky hose - or as an emergency adapter for the connection of two hose lines with different threads in situations where pressures do not exceed 150 psi (10.34 bar).

- Akrolite® construction and molded neoprene liner
- Fits all 2 1/2" (64 mm) hose from 2 3/4" (70 mm) to 3 5/16" (84 mm) O.D.
- Length: 13" (330 mm), weight: 16 1/2 lbs. (7.5 kg)

#### 773 3" (76 mm) Hose Jacket

- Same as Style 772, except: Fits 3" (76 mm) hose from 3 1/2" (89 mm) to 3 3/4" (95 mm) O.D.
- Length: 15" (381 mm), weight: 26 3/4 lbs. (12.1 kg)

#### 352 2 1/2" (64 mm) Hose Jacket Mounting Peg

- For mounting 2 1/2" (64 mm) hose jacket on a running board or in a compartment
- Length: 13 3/8" (340 mm), weight: 2 1/4 lbs. (1 kg)

#### 353 3" (76 mm) Hose Jacket Mounting Peg

- Same as Style 352, except for 3" (76 mm) hose jacket
- Length: 15 1/2" (394 mm), weight: 3 3/4 lbs. (1.7 kg)



Style 772

### Hose Clamp

#### 588 Hose Clamp

- For use on double-jacketed woven hose up to 3" (76 mm)
- Rubber jaws and lock
- Lightweight for easy handling
- Supplied with Style 589 mounting bracket
- Length: 30" (762 mm), weight: 16 lbs. (7.3 kg)

#### 589 Hose Clamp Mounting Bracket

- For Style 588 Hose Clamp



Style 588

## Tool Kit

### 9200 Nozzle Repair Tool Kit

The Nozzle Repair Tool Kit contains the essential tools for Akron Brass nozzle repair. All tools are packaged in a sturdy carrying bag. The repair kit is warranted for 1 year.

- Tools include:
  - 3 Swivel Adapter Tools and Rod
  - Akron Brass logoed carrying bag



Style 9200

## Equipment Holders

### 350 Mounting Plate

- Chrome plated
- Available in 1.5", 2.5", 3.5", 4.5" & 6"
- NH Only
- For securing equipment with female threads
- Screw type mount with bolt holes in the center for neat appearance
- 2 1/2" (64 mm) weight: 12 oz. (340 g)



Style 350

### 373 E-Z - Lok Nozzle Holder

- Available in 1 1/2" (38 mm) and 2 1/2" (64 mm) sizes - Must specify
- For securing equipment with female threads
- Quick release for fast and easy mounting and removal
- Weight: 1 5/8 lbs. (.7 kg)



Style 373

## Sprinkler Shutoff

### 1078 Quickfit Sprinkler Shutoff

Simple, quick, positive shutoff for many types of sprinkler heads with openings of approximately 7/8" (22 mm) wide by 1" (25 mm) high or 3/4" (19 mm) wide by 1 1/16" (43 mm) high. Allows sprinkler heads out of fire area to be shut off. Weight: 6 oz. (170 g)



Style 1078



### Lubricants

Repair instructions for Akron® products often call for lubricants to ensure proper repair and long term service.

- 9201 Parker® O-Lube**
  - 4 oz. (113 g) tube
- 9202 Low-Temp Lubriplate® Grease**
  - 10 oz. (284 g) tube
- 9203 Low-Temp Lubriplate® Grease**
  - 14 1/2 oz. (411 g) cartridge
- 9210 Mobilith SHC 460 Synthetic Grease**
  - 13.7 oz. (390g) tube



Style 9201

Style 9202

Style 9203

Style 9210

### Hose Accessories

- 583 Hose Hoist**
  - Akrolite™ construction
  - For raising or lowering hose, ladders, etc. to and from the roof or through windows
  - Weight: 7 1/8 lbs. (3.4 kg)
- 78 Hose & Ladder Strap**
  - Secures hose up to 3" (76 mm) on ladders, fire escapes, etc. and aids in the handling of hose
  - Anodized aluminum fittings with 1" (25 mm) wide, flat, water-resistant nylon webbing
  - Fits ladder rungs up to 2" (51 mm) O.D.
  - Weight: 1 lbs. (.5 kg)



Style 78

Style 583