

# News Bulletin

Product Update



9/04/13

**PRODUCT NAME: GP Manual Monitor**

**AKRON PART NUMBER: 3430**

## **PRODUCT DESCRIPTION**

---

The GP Manual Monitor is one of the most cost effective, highest performing, firefighting monitors found in the world and it is **now available in 2.5" or 3" NPT or BSPT threaded inlets.**



## **FEATURES**

---

- Now available in 2.5" or 3" NPT or BSPT threaded inlets in addition to the 3" ASA or DIN 80 flanged inlet
- Cast-in turning vanes and integrated removable stream shaper for maximum reach and stream performance
- Built-in pressure gauge
- Compact, efficient design requires minimum mounting space

## **PRODUCT STATISTICS**

---

- Rated flow up to 1000 gpm (3800 lpm)
- Continuous 360° rotation
- Elevation +90° to -45°

## **LIST PRICE (US Dollars, FOB Wooster, OH USA)**

---

Monitor only, less nozzle .....\$1,400.00

## **AVAILABILITY**

---

Currently available

## **SPECIFICATION**

---

The 1000 gpm rated monitor shall have a 2.5" or 3" NPT or BSPT inlet, 2.5" waterway with a 2.5" NH discharge outlet. The discharge outlet shall have a built-in stream shaper element. The vertical and horizontal travel locks shall incorporate round manual knobs. A "T" handle tiller bar shall be provided for vertical and horizontal position adjustment. Enhanced, compact design provides for less tip weight which translates to lower handle operating force. The monitor height shall not exceed 14-3/4" from the flange to the top of the outlet elbow (less nozzle) when in the vertical position. All elbows shall have cast-in turning vanes. The monitor shall have a vertical travel of 135° and horizontal travel of 360°.