

PHONE: 800.228.1161 | www.akronbrass.com

WARRANTY AND DISCLAIMER*: We warrant Akron Brass products for a period of five (5) years* after purchase against defects in materials or workmanship. Akron Brass will repair or replace product which fails to satisfy this warranty. Repair or replacement shall be at the discretion of Akron Brass. Products must be promptly returned to Akron Brass for warranty service. We will not be responsible for: wear and tear; any improper installation, use, maintenance or storage; negligence of the owner or user; repair or modification after delivery; failure to follow our instructions or recommendations; or anything else beyond our control. WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, OTHER THAN THOSE INCLUDED IN THIS WARRANTY STATEMENT, AND WE DISCLAIM ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. Further, we will not be responsible for any consequential, incidental or indirect damages (including, but not limited to, any loss of profits) from any cause whatsoever. No person has authority to change this warranty. *Unless otherwise provided herein. Akron Brass industrial electronic components & the Severe-Duty Monitor have a one (1) year warranty. Select Akron Brass handline nozzles and valves carry a ten (10) year warranty. Select Weldon LED products carry a five (5) year warranty. Honda products have a two (2) year warranty from date of manufacture (excluding consumable components). Select Weldon LED products carry a five (5) year warranty. Honda products have the manufacturers' warranty and Akron Brass disclaims any warranty in respect of those products.

© 2016 Akron Brass Company. All rights reservered. No portion of this can be reproduced without the express written consent of the Akron Brass Company.

Parts List Sheet:

22663

BODY NOZZLE

SPRING LEE

GASKET

SLEEVE PATTERN

SWIVEL 1.5"NH

PLUG SWIVEL

TEETH TURBINE

RING RETAINER

O-RING 2-235

O-RING 2-122

SCREW ACME

O-RING 2-127

BALL 3/16" SST

GEAR BALLSCREW

NUT HEX 1/4-20

O-RING 2-029

O-RING 2-015

PIN ROLL 1/16 x 3/8"

SHIM PLASTIC GREEN

SHIM PLASTIC BROWN

SHIM PLASTIC BLUE

SHIM PLASTIC PINK

BAND ID 12v

BAND ID 24v

WORM PATTERN ACTUATOR

MOTOR 12V SUBASSEMBLY

MOTOR 24V SUBASSEMBLY

SCREW SOCKET HEAD CAP 6-32 x 1/2"

HOUSING SCREW

HOUSING SCREW - FDP

O-RING 2-155

BALL BRASS 1/4"OD

STEM BAFFLE ADJUSTABLE

Find

1 3

3

4

5

6

7

8

9

10

11

12

13

14

14

15

15

15

16

19

19

20

22

23

23

24

25

26

27

28

29

30

34

35

36

36

39

40

41

42

43

44

44

В

@

@

@

@

* * *

* * *

* * *

* * *

А

А

TECHNICAL SERVICE PARTS

STYLE

Description

HEAD BAFFLE ADJUSTABLE 300 GPM / 1140 LPM

HEAD BAFFLE ADJUSTABLE 350 GPM / 1325 LPM

PIN GROOVE 1/4 " x 1" (ADJUSTABLE BAFFLE)

SCREW SOCKET HEAD SHOULDER 1/2D x 1"LG x 3/8-16

O-RING 2-153 (OPTIONAL FLAT DISPERSED PATTERN)

RING RETAINER (OPTIONAL FLAT DISPERSED PATTERN)

SCREW SOCKET HEAD FLAT POINT SET 5/16-24 x 1/4"

PATTERN SLEEVE RING (NO TEETH)

TUBE GUIDE PATTERN ACTUATOR

TUBE GUIDE PATTERN ACTUATOR - FDP

3293

IF AN ITEM IS NOTED AS "NOT FIELD REPAIRABLE", OR YOU WISH TO RETURN AN ITEM TO AKRON BRASS FOR SERVICE PLEASE GO ONLINE TO, ONLINEREPAIR.AKRONBRASS.COM

PRODUCT 125-350 GPM FORESTRY NOZZLE

Item

118332

122360

118330

768318

768319

744273

118333

717042

115424

-

765198

742023

772171

757359

757327

118964

118454

120406

757046

122669

126364

757335

765344

122668

126363

757048

-

765134 718298

734061

785021

744341

757056

757112

33560006

33560008

765150

768308

768218

768219

768220

703563

703564

OTY

1

1

1

1

1

1

1

1

1

25

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

1

24

1

1

1

1

1

1

1

1

6

1

1

1

| Find | Description | ltem | QTY |
|------|--|--------|-----|
| 51 | NUT ACME SCREW | 734115 | 1 |
| 52 | WASHER | 784210 | 2 |
| 53 | WASHER BELEVILE | 784071 | 2 |
| 54 | SCREW SOCKET HEAD CUP POINT #10-32 x 1" | 765168 | 1 |
| 55 | SCREW SOCKET HEAD CUP POINT SET #10-32 x 3/16" | 765177 | 1 |

| 52 | |
|----|-----------|
| | \langle |
| | |
| | |
| | |

| IN |
|----|
| 1. |
| |


** FOR OTHER FLOW RATES CONTACT CUSTOMER SERVICE. *** INSTALLED AT FACTORY AS NEEDED FOR FINAL FLOW CALIBRATION. @ ITEMS 29 AND 30 INCLUDED WITH MOTOR SUBASSEMBLY ITEM 36.

PHONE: 800.228.1161 | www.akronbrass.com

WARRANTY AND DISCLAIMER*: We warrant Akron Brass products for a period of five (5) years* after purchase against defects in materials or workmanship. Akron Brass will repair or replace product which fails to satisfy this warranty. Repair or replacement shall be at the discretion of Akron Brass. Products must be promptly returned to Akron Brass for warranty service. We will not be responsible for: wear and tear; any improper installation, use, maintenance or storage; negligence of the owner or user; repair or modification after delivery; failure to follow our instructions or recommendations; or anything else beyond our control. WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, OTHER THAN THOSE INCLUDED IN THIS WARRANTY STATEMENT, AND WE DISCLAIM ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. Further, we will not be responsible for any consequential, incidental or indirect damages (including, but not limited to, any loss of profits) from any cause whatsoever. No person has authority to change this warranty. *Unless otherwise provided herein. Akron Brass industrial electronic components & the Severe-Duty Monitor have a one (1) year warranty. Select Akron Brass handline nozzles and valves carry a ten (10) year warranty. Scene Star Lights carry a (6) year warranty. Weldon products have a two (2) year warranty from date of manufacture (excluding consumable components). Select Weldon LED products carry a five (5) year warranty. Honda products have the manufacturers' warranty and Akron Brass disclaims any warranty in respect of those products.

© 2016 Akron Brass Company. All rights reservered. No portion of this can be reproduced without the express written consent of the Akron Brass Company.

| Chg. | Date |
|------|-------|
| 08 | 04-19 |
| 09 | 07-22 |
| | |



"IMPORTANT" ISTALLATION INSTRUCTIONS

To set gallonage, push in on the baffle head and rotate until desired setting aligns with the roll pin. Note: Nozzle may need to be in flush to change to the lowest gallonage.

MAXIMUM OPERATING PRESSRE: 200 PSI FLOW RATING: 125-300 GPM AT 100 PSI

WARNING: The electric control system must incorporate a current limiting circuitry set for a maximum of 3 amps for 12 volts (1.5 amps for volts). Without circuitry set, motor may become inoperable if stalled during operation.

Parts List Sheet:

122663

D45959