Light Head Only Order Form



STEP 1: SELECT YOUR LIGHT HEAD

Select the appropriate light head for your available power supply (AC or DC).

		AC (generator	or shore	-powere	d)		
Description	Select One	Light Head	Lumens	Voltage	Wattage	Certifications	Head Height
SceneStar		ELSS-XLAC	20,000	120	220	UL, ROHS, CSA	12"
		ELSS-XLAC2	20,000	240	220	CE, ROHS	12"
		DC (truck b	attery-po	owered)			
Description	Select One	Light Head	Lumens	Voltage	Wattage	Certifications	Head Height
SceneStar		ELSS-SLDC	14,000	10-32	150	CE, ROHS	12"
		ELSS-XLDC	19,000	10-32	220	ROHS	12"
Revel (ELRE-XLDC shown below)		ELRE-SLDC	14,000	10-32	110	ROHS	10.75"
(LENE-ALDC SHOWN BEIOW)		ELRE-XLDC	28,000	10-32	220	ROHS	10.75"

STEP 2: SELECT ACCESSORIES

Handla/Cuival Ontion

П	andie/Swiver Options
	Head with handle & swivels (standard)
	Head only with no handle or swivels
	Sealed & Vented ELSS w/ Strain Relief for Tower Mounting
	Head with no bottom handle - has top handle and swivel
Ac	dapters Needed for Competitor Pole?
Ac	No adapter needed No adapter needed
	· · · · · · · · · · · · · · · · · · ·
	No adapter needed
	No adapter needed FRC Pole Adapter
	No adapter needed FRC Pole Adapter HAVIS/ROM Pole Adapter