



THIS DRAWING AND ALL INFORMATION CONTAINED HEREIN IS THE PROPERTY OF WELDON TECHNOLOGIES, INC. AND MAY NOT BE COPIED, REPRODUCED, OR DEVULGED TO UNAUTHORIZED PERSONS WITHOUT THE EXPRESS WRITTEN CONSENT OF WELDON TECHNOLOGIES, INC. AS IT IS BEING PROVIDED SOLELY FOR THE CONVENIENCE OF THE USER AND SHALL BE RETURNED TO WELDON TECHNOLOGIES, INC. UPON REQUEST.

REVISIONS				
REV.	ECN	DESCRIPTION	DATE	BY / APVD
A	R0902	RELEASE FOR PRODUCTION	8/4/09	TB / ST



- NOTES:
- LED WARNING LAMP ASSEMBLY PART NUMBERS:
RED = 1020-9000-10
AMBER = 1020-9000-20
 - EXCEEDS J887 REQUIREMENTS FOR PHOTOMETRIC INTENSITY AND FLASH ENERGY.
 - COMPLIES WITH FMVSS 108.
 - INPUT VOLTAGE RANGE: 10-16VDC
 - CURRENT DRAW:
RED = 0.70A-0.90 PEAK
AMBER = 1.25A-1.45A PEAK
 - OPERATING TEMPERATURE RANGE: -40 TO +65C

- FEATURES:
- 5-YEAR WARRANTY
 - FULLY SERVICEABLE (L.E.D., COVER LENS, LENS GASKET, MOUNTING GASKET)
 - CAST ALUMINUM HOUSING
 - AUTOMOTIVE GRADE OUTER LENS, MEETS SAE J576
 - LARGE, FLAT SEALING SURFACE
 - CLOSED-CELL FOAM MOUNTING PAD IS ADHERED TO BACK OF LAMP
 - CONSTANT CURRENT LED DRIVER CIRCUIT MAINTAINS LED BRIGHTNESS ACROSS INPUT VOLTAGE RANGE
 - MEETS LEVEL 4 EMISSIONS AND 100V/M SUSCEPTABILITY TESTS
 - OVERVOLTAGE SHUTDOWN (>20V)
 - FULL TRANSIENT PROTECTION (SAE J1113)
 - FAIL-SAFE FLASH MODE (LAMP WILL FLASH SLOWLY IF CONSTANT POWER IS APPLIED IN STEADY FLASH MODE)
 - STROBING FLASH PATTERN SELECTABLE (APPLY GROUND TO BLACK WIRE)



WIRING TABLE			
FUNCTION	RED WIRE	BLACK WIRE	WHITE WIRE
STEADY FLASH	POWER (+)	N/C	GROUND (-)
STROBING FLASH	POWER (+)	GROUND (-)	GROUND (-)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: X.XXX - ±0.005 X.XX - ±0.020 X.X - ±0.10 ANGLES - ±0.5°	CAD GENERATED DRAWING. DO NOT MANUALLY UPDATE		WELDON TECHNOLOGIES, INC.	
	APPROVALS	DATE		
MATERIAL	DRAWN TB	2/6/09	7" DIA J887 LED WARNING LAMP GROUND ENABLE STROBE MODE 3-WIRE	
FINISH	CHECKED ST	8/4/09		
DO NOT SCALE DRAWING	PROJ. NO.	00125-2	SIZE B	PART NO. C1020-9000-00
			SCALE: 1:2	REV. A