



MATING CONNECTOR: DT06-4S

POSITION	CIRCUIT	INPUT/OUTPUT
A1	IGNITION POWER	(+) SYSTEM POWER
A2	ACCESSORY GROUND	(-) SYSTEM GROUND
A3	PLUG	NC
A4	PLUG	NC

MATING CONNECTOR: DT06-12S

POSITION	CIRCUIT	INPUT/OUTPUT
B1	REFERENCE +5 VDC	+5VDC INPUT
B2	THROTTLE INTERLOCK	12VDC INPUT
B3	HIGH IDLE	12VDC INPUT
B4	CAT SELECT	12VDC INPUT
B5	SIGNAL GROUND	TRANSDUCER GROUND OUTPUT
B6	SIGNAL VOLTAGE	TRANSDUCER 5VDC OUTPUT
B7	SIGNAL IN	TRANSDUCER SIGNAL INPUT
B8	CONTROL OUT	CONTROL SIGNAL OUTPUT
B9	REFERENCE GROUND	GROUND INPUT
B10	PUMP ENGAGE INTLK	12VDC INPUT
B11	DELAY RELAY COMMON(CO)	ENABLE INPUT
B12	DELAY RELAY NO (B7)	ENABLE OUTPUT

DRAWING NOTES:
1. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES.
2. Do not scale drawing.
3. Decimal Tolerance .XXXX = +/- .005.
4. Angle Tolerance .5 deg.

This document and the information contained herein are the exclusive property of Class 1 and is loaned to you subject to return on demand, unless otherwise agreed to in writing by Class 1.

A unit of
Class 1
INDEX CORPORATION
607 N.W. 27th Ave.
Ocoee, Florida 34475
Phone 352-629-5020
FAX 352-629-2902

UNI-GOVERNOR CONTROL

CAGE IDENT. NO. 08C64	COMPLETED 03/19/2002	DRAWN BY G.M.C.	CHECKED ---	DPP ---
SIZE A	DRAWING NUMBER 107396			REV D
SCALE NONE				SHEET 4 OF 4